DDR2 2G 800 1.8V SO-DIMM

2GB 256M x 64-Bit DDR2-800

CL6 200-Pin SODIMM

DESCRIPTION

This document describes ValueRAM's 256M x 64-bit 2GB (2048MB) DDR2-800 CL6 SDRAM (Synchronous DRAM) memory module. The components on this module include sixteen 128M x 8-bit DDR2-800 SDRAM in FBGA packages. This 200-pin SODIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

SPECIFICATIONS

Clock Cycle Time (tCK) CL=6	2.5ns (min.) / 8ns (max.)
Row Cycle Time (tRC)	60ns (min.)
Refresh to Active/Refresh Command Time (tRFC)	127.5ns
Row Active Time (tRAS)	45ns (min.) / 70,000ns (max.)
Single Power Supply of	+1.8V (+/- .1V)
Power	1.584 W (operating)
Main Chips	Hynix, Samsung, Micron
UL Rating	94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here.

Figure 1: DDR2 2G 800 1.8V SO-DIMM

(units = millimeters)